
AUBURN PRODUCT NEWS

Auburn Manufacturing Company

29 Stack Street

Middletown, CT 06457

Tel: 860-346-6677, Fax: 860-346-1334

website: www.auburn-mfg.com

email: info@auburn-mfg.com

MP-15 Pro-Formance[®]/MicroPore[®] Gasket Material

Specification Data Sheet

F729000M5

Description

MP-15 from Auburn is designed for heavy-duty applications including compressors, diesel engines, and others. It has excellent low flange pressure sealability and bolt torque retention. It is intended for applications with short duration maximum temperatures up to 205°C (400°F).

Property:

Specification:

Method:

Density , g/cc (lb/cu. ft.)	1.54 (96) (min.)	ASTM F 1315
Compressibility , % (at 34.5Mpa)	13 – 25	ASTM F 36
Recovery , %	50 (min.)	ASTM F 36
Tensile Strength , AMD,Mpa (psi)	10.34 (1500) (min.)	ASTM F 152
Binder Type	Polychloroprene	

Remarks and related documents:

Specification Values determined by test methods required for ASTM F-104. Type 7 materials.

Ordering Information: MP-15 is available in thicknesses of .015", .020", .025", .031", .047" and .062", in rolls @ 40" wide continuous length or sheets @ 40" x 36". **Auburn can die cut, stamp, slit-to-width, strip, sheet, or apply pressure sensitive adhesive to MP-15 in accordance with your exact specifications.**

GASKETS • PADS • SEALS • BUSHINGS • SPACERS
