



PRODUCT NEWS

Auburn Manufacturing Company

29 Stack Street, Middletown, CT 06457
PHONE 860-346-6677 FAX 806-346-1334
Email: info@auburn-mfg.com
Website: www.auburn-mfg.com

CLOTH-INSERTED (CI) SBR RUBBER REGULAR POLYESTER PLY

Cloth reinforcement enhances dimensional stability in flanged gasket applications with high compression loads. Suitable for use in air, hot water, low pressure steam, and hydraulic services. An SBR compound reinforced with a close weave polyester fabric. This construction includes one ply of fabric for each 1/16" thickness.

Temperature Range: -30°F to +170°F

- Width: 36", 48"
- Trim: Trimmed
- Finish: Smooth
- Color: Black
- **Fabric Type: 4.0 oz Polyester**

Typical Properties:

Durometer Hardness (Shore A ± 5)	Product Number	Thickness (inches)	Tensile (psi)	Ultimate Elongation (%)	Estimated Weight per Linear Foot (1/8" X 36") (lb)	Features
65	AUB65CI	.062 – .250	1500	350	2.74	Polyester Inserted Sheet

GAUGES: This construction includes one ply for each 1/16" thickness:
1/16 - 3/32 = 1 ply; 1/8" = 2 plies; 3/16" = 3 plies; 1/4" = 4 plies

These typical physical properties are provided for evaluation information only. It is up to the end-user to determine the appropriate material for the intended application.

GASKETS • PADS • SHEETS • ROLLS • SHIMS • SEALS • TAPES