



PRODUCT NEWS

Auburn Manufacturing Co.
 29 Stack St., Middletown, CT 06457
 Phone (860) 346-6677 FAX (860) 346-1334
 www.auburn-mfg.com
 email:info@auburn-mfg.com

JUST RELEASED: NEW PORON® - FLAME RETARDANT CELLULAR URETHANE FOAM

Product Availability: Standard Industrial Materials

Effective: May 1, 1997
 (Supersedes November 1, 1996)

PORON® 4701-21: LOW POROSITY (SOFT)

COLOR: BLACK (1604)

PRODUCT	ROLL SIZE									
	THICKNESS		WIDTH		LENGTH		TOTAL		APPROX. WEIGHT	
	inches	mm	inches	mm	feet	m	sq. ft.	sq. m.	lbs.	kg.
4701-21-20062-1604	1/16	1.57	54	1,372	300	91	1,350	125	142	64
4701-21-20093-1604	3/32	2.36	54	1,372	225	69	1,012	94	154	70
4701-21-20125-1604	1/8	3.18	54	1,372	165	50	742	69	154	70
4701-21-15188-1604	3/16	4.78	54	1,372	100	30	450	42	103	47
4701-21-15250-1604	1/4	6.35	54	1,372	80	24	360	33	108	49
4701-21-15375-1604	3/8	9.53	38	965	60	18	190	18	90	41
4701-21-15500-1604	1/2	12.70	38	965	40	12	127	12	80	36

PORON® 4701-30: VERY LOW MODULUS (VERY SOFT)

COLOR: AZURE (1648)

(Replaces 4701-59)

4701-30-25035-1648	1/32	0.89	40	1,016	150	46	500	46	35	16
4701-30-25045-1648	3/64	1.14	40	1,016	150	46	500	46	45	20
4701-30-25062-1648	1/16	1.57	42	1,067	300	91	1,050	98	110	50
4701-30-20093-1648	3/32	2.36	42	1,067	225	69	787	73	120	54
4701-30-20125-1648	1/8	3.18	42	1,067	165	50	577	54	120	54
4701-30-15188-1648	3/16	4.78	42	1,067	100	30	350	33	80	36
4701-30-15250-1648	1/4	6.35	40	1,016	80	24	266	25	80	36
4701-30-15375-1648	3/8	9.53	38	965	60	18	190	18	90	41
4701-30-15500-1648	1/2	12.70	38	965	40	12	127	12	80	36

PORON® 4701-40: LOW MODULUS (SOFT)

COLOR: BLACK (1604)

(Replaces 4701-01, 4716-01, -16 & 71)

4701-40-20062-1604	1/16	1.57	54	1,372	300	91	1,350	125	125	142
4701-40-20093-1604	3/32	2.36	54	1,372	225	69	1,012	94	94	154
4701-40-20125-1604	1/8	3.18	54	1,372	165	50	742	69	1544	70
4701-40-15188-1604	3/16	4.78	54	1,372	100	30	450	42	1033	47
4701-40-15250-1604	1/4	6.35	54	1,372	80	24	360	33	1088	49
4701-40-15375-1604	3/8	9.53	38	965	60	18	190	18	90	41
4701-40-15500-1604	1/2	12.70	38	965	40	12	127	12	80	36

PORON® 4701-50: HIGH MODULUS (FIRM)

COLOR: BLACK (1604) GRAY (1637)

(Replaces 4701-05)

4701-50-30017-1637	-	0.43	40	1,016	600	183	2,000	186	85	39
4701-50-30031-1637	1/32	0.79	54	1,372	150	46	675	63	54	25
4701-50-30045-1637	3/64	1.14	54	1,372	150	46	675	63	74	34
4701-50-20062-1637	1/16	1.57	54	1,372	300	91	1,350	125	142	64
4701-50-20125-1637	1/8	3.18	54	1,372	165	50	742	69	154	70
4701-50-15250-1637	1/4	6.35	54	1,372	80	24	360	33	108	49

Please see additional materials listed on the reverse side.

Product Availability: Standard Industrial Materials - Continued

Effective: May 1, 1997
(Supersedes November 1, 1996)

PORON® 4701-60: VERY HIGH MODULUS (VERY FIRM)

COLOR: BLACK (1604)

(Replaces 4701-12 & 13)

PRODUCT	ROLL SIZE									
	THICKNESS		WIDTH		LENGTH		TOTAL		APPROX. WEIGHT	
	inches	mm	inches	mm	feet	m	sq. ft.	sq. m.	lbs.	kg.
4701-60-25031-1604	1/32	0.79	42	1,067	150	46	525	49	38	17
4701-60-25062-1604	1/16	1.57	42	1,067	150	46	525	49	76	34
4701-60-25125-1604	1/8	3.18	42	1,067	166	50	577	54	152	68
4701-60-20062-1604	1/16	1.57	42	1,067	150	46	525	49	59	25
4701-60-20125-1604	1/8	3.18	42	1,067	165	50	577	54	120	54
4701-60-20250-1604	1/4	6.35	40	1,016	80	24	267	25	107	49
4701-60-15125-1604	1/8	3.18	42	1,067	155	50	577	64	96	43
4701-60-15250-1604	1/4	6.35	40	1,016	80	24	267	25	80	36

PORON® 4723-43: HIGH TEMPERATURE (SOFT)

COLOR: BLACK (1610)

(Replaces 4723-23)

4723-43-20125-1610	1/8	3.18	42	1,067	165	50	577	54	120	54
4723-43-15188-1610	3/16	4.78	42	1,067	100	30	350	22	80	36
4723-43-15250-1610	1/4	6.35	40	1,067	80	24	266	25	80	36

AVAILABILITY OF INDUSTRIAL MATERIALS

PORON® Industrial Products are produced on a "make to order" basis. Although off-the-shelf stock may be available for standard grades and thicknesses, normal lead time is two to four weeks. Check with our Customer Service Representative for your specific requirements.

PRODUCT WIDTH

Most Industrial materials are trimmed to stated width +1 inch - 0. Untrimmed materials are available on special order.

*This product is provided untrimmed offering a minimum of 40" of useable material.

BUFFING

Many PORON® products can be buffed to remove the skin. Buffed thickness tolerance will be +/-5% on thicknesses down to .080" and +/- .004" on thicknesses less than 0.080".

- Minimum order for buffing is one standard roll.

Note: Buffing is available on materials up to 48" wide.

NON-STANDARD MATERIALS

For non-standard thicknesses, widths, and/or colors apply the following minimum order size. (For available colors see color card) Custom colors are available and may require higher minimum orders and color matching charges. Ask your Customer Service Representative.

For non-standard industrial materials the following minimum order quantities apply per item.	
Thickness < 3/16" (4.78 mm)	Minimum 4000 ft ² (372m ²)
≥ 3/16" (4.78 mm)	3000 ft ² (279m ²)
Combining of non-standard items to achieve lower price/quantity discounts is not permitted.	

PORON® is a registered trademark.
For more information call
Auburn Manufacturing Company (800) 427-5387