

# AUBURN PRODUCT NEWS

## Auburn Manufacturing Co.

29 Stack St., Middletown, CT 06457

Phone (860) 346-6677 FAX (860) 346-1334

[www.auburn-mfg.com](http://www.auburn-mfg.com)

email: [info@auburn-mfg.com](mailto:info@auburn-mfg.com)

## STRIP-N-STICK<sup>®</sup> 200A (Silicone Sponge Tape)

### General Description

**STRIP-N-STICK<sup>®</sup> 200A** from Auburn offers the compressibility of a medium compression **COHRLastic<sup>®</sup>** closed cell sponge with an acrylic pressure-sensitive adhesive on one side. **STRIP-N-STICK<sup>®</sup> 200A** offers superior service life, excellent conformability, and flexibility. Other benefits include low compression set and high adhesion to a variety of substrates. **STRIP-N-STICK<sup>®</sup>** is often chosen for high-low temperature resistance, gasketing, vibration damping, and thermal insulation.

### Typical Properties

Thickness Available (Inches)	.031, .062, .093, .125, .187, .250, .375, .500
Silicone Rubber Material Type	Silicone Sponge
Adhesive Type	Acrylic
Adhesion (oz./inch width)	30
Tensile Strength (lbs/inch)	65
Elongation (%)	150
Compression Deflection (comp. 75% of original)	10
Compression Set % (50 % compression, 22 hours @ 212°F)	25
Adhesive Shelf Life	24 months
Temperature Range, Sponge (°F)	-100°F - +500°F
Temperature Range, Adhesive (°F)	-20°F - +325°F
Color	Orange/Tan

#### Notes:

Values shown are typical and should not be used for writing specifications.

### Ordering Information

Thicknesses of .031", .062", .093", .125" are available in standard 10-yard rolls. Thicknesses of .187", .250", .375" & .500" are available in standard 5-yard rolls. Other colors, in addition to those listed here, are available upon request. Auburn can slit master logs into narrower rolls ranging in width from 1/4" thru 36" wide. All rolls come with an *easy-to-remove peel-off liner* on the adhesive side. To obtain more information about **STRIP-N-STICK<sup>®</sup>**, please contact your Auburn Customer Service Representative.