

AUBURN PRODUCT NEWS

Auburn Manufacturing Co.

29 Stack St., Middletown, CT 06457

Phone (860) 346-6677 FAX (860) 346-1334

www.auburn-mfg.com

email: info@auburn-mfg.com

STRIP-N-STICK[®] 300AR (Fiberglass Reinforced Silicone Sponge Tape)

General Description

STRIP-N-STICK[®] 300AR from Auburn offers the unique construction of a reinforced medium compression COHRLastic[®] closed cell silicone sponge with an acrylic pressure-sensitive adhesive on one side. STRIP-N-STICK[®] 300AR offers superior service life, excellent conformability, and flexibility. Other benefits include low compression set and high adhesion to a variety of substrates. STRIP-N-STICK[®] 300AR is often chosen for high-low temperature resistance, vibration damping, and/or thermal insulation.

Typical Properties

Thickness Available (Inches)	.062, .125", .187"
Silicone Rubber Material Type	Fiberglass reinforced sponge
Adhesive Type	Acrylic
Adhesion (oz./inch width)	30
Tensile Strength (lbs/inch)	180
Elongation (%)	<10
Compression Deflection (comp. 75% of original)	15
Compression Set % (50% compression, 22 hrs. @ 212 F)	25
Adhesive Shelf Life	24 months
Temperature Range, Solid (°F)	-100°F - +500°F
Temperature Range, Adhesive (°F)	-20°F - +325°F
Color	Blue/Gray

Notes:

Values shown are typical and should not be used for writing specifications.

Ordering Information

Thicknesses of .062" and .125" are supplied in standard 10-yard rolls. Thickness of .187" is available in a 5-yard roll. Other colors, in addition to those listed here, are available upon request. Auburn can slit master logs into narrower rolls ranging in width from ¼" thru 36" wide. All rolls come with an *easy-to-remove peel-off liner* on the adhesive side. To obtain more information about STRIP-N-STICK[®], please contact your Auburn Customer Service Representative.