

AUBURN PRODUCT NEWS

Auburn Manufacturing Co.

29 Stack St., Middletown, CT 06457

Phone (860) 346-6677 FAX (860) 346-1334

www.auburn-mfg.com

email: info@auburn-mfg.com

STRIP-N-STICK[®] 512AF (Silicone Foam Tape)

General Description

STRIP-N-STICK[®] 512AF from Auburn offers the compressibility of a modified cell **COHRIlastic[®]** silicone fire blocking foam with a film supported acrylic adhesive on one side. **STRIP-N-STICK[®] 512AF** offers superior service life, excellent conformability, and flexibility. Other benefits include low compression set and high adhesion to a variety of substrates. **STRIP-N-STICK[®]** is often chosen for high-low temperature resistance, gasketing, vibration damping, and thermal insulation.

Typical Properties

Thickness Available (Inches)	.062, .093, .125, .187, .250, .375, .500
Silicone Rubber Material Type	Open cell foam
Adhesive Type	Film-supported acrylic
Adhesion (oz./inch width)	30
Tensile Strength (lbs/inch)	20
Elongation (%)	75
Adhesive Shelf Life	24 months
Temperature Range, Foam (°F)	-100°F - +500°F
Temperature Range, Adhesive (°F)	-20°F - +325°F
Color	Gray

Values shown are typical and should not be used for writing specifications.

Ordering Information

Thicknesses of .062", .093", .125" are available in standard 10-yard rolls. Thicknesses of .187", .250", .375" & .500" are available in standard 5-yard rolls. Other colors, in addition to those listed here, are available upon request. Auburn can slit master logs into narrower rolls ranging in width from 1/4" thru 36" wide. All rolls come with an *easy-to-remove peel-off liner* on the adhesive side. To obtain more information about **STRIP-N-STICK[®]**, please contact your Auburn Customer Service Representative.