AUBURN PRODUCT NEWS

Auburn Manufacturing Company 29 Stack Street, Middletown, CT 06457 Customer Service: (800) 427-5387 Tel: (860) 346-6677 Fax: (860) 346-1334 website: www.auburn-mfg.com < Click Link to Learn More e-mail: info@auburn-mfg.com

SAE F-26 WOOL FELT (Typical Properties)

F-26 Felt is used for insulating seals, packings, gaskets and bushings. **F-26 Felt** is 40% wool, light in weight, and easy to die-cut into specific shapes. **F-26 Felt** readily accepts pressure-sensitive adhesive. Sheets or rolls, in addition to die-cut parts, are available either plain or with an adhesive-backing applied to one or both sides. **F-26 Felt** can be supplied in any thickness between 1/64" and 4.00". **F-26 Felt's** standard color is grey.

General Properties Wool Content (fiber basis), min. % 40 Density (1"), ibs/sq yd 7.2 Standard Thickness Range, in. 1/64* thru 4.00" Standard Michness Range, in. 72 Color grey Physical Properties 72 Specific Gravity (%) 17 Therm. Cond. (70F), btu/hr/sq ft%F/in. 0.25 Thermal Expansion 0 Air Perm (1/16"), cfm/sq ft/0.5"H2O 100-200 Liquid Absorption % by weight (1.0 sp gr) >400 Liquid Absorption % by weight (1.0 sp gr) >400 Coef. of Friction Coef. of Friction Vibration Absorption _static load bearing cap/unit area very low Noise Reduction Coef. (1") 0.66 Mechanical Properties Tensile Strength (min), psi Hardness Range, Shore A 5-15 Compressibility(10% Deflection), psi 1 Hardness Range, Shore A 5-15 Compressibility 10% Deflection), ps	Commercial Standard Grade SAE Number NTA Number		8R5 F-26 17R2
Wool Content (fiber basis), min. % 40 Density (1"), Ibs/keg vd 7.2 Standard Thickness Range, in. 72 Color grey Physical Properties 72 Specific Gravity (%) 17 Therm. Cond. (70F), btu/hr/sq ft/%F/in. 0.25 Thermal Expansion 0 Air Pern (1/16"), oftru/sq ft/0.5"H ₄ O 100-200 Liquid Absorption % by weight (1.0 sp gr) >4400 Liquid Absorption % by veight (1.0 sp gr) >4400 Coef. of Friction 0 Coef. of Friction 92 Vibration Absorption static load bearing cap/unit area very low Noise Reduction Coef. (1") 0.65 Molen Bursting Strength (1/8"), psi 25 Split Resistance (min), psi Split Resistance (min), psi Horden Coef of Triction Multen Bursting Strength (1/8"), psi 25 Split Resistance (min), b/2" width	General Properties		
Density (1"), Ibs/sq yd 7.2 Standard Thickness Range, in. 1/64" thru 4.00" Standard Width, in. 72 Color grey Physical Properties grey Specific Gravity (%) 17 Therm. Cond. (70F), btu/hr/sq ft/ºF/in. 0.25 Thermal Expansion 0 Air Perm (1/16"), cfm/sq ft/0.5"H ₂ O 100-200 Liquid Absorption % by weight (1.0 sp gr) >4400 Liquid Absorption % by weight (1.0 sp gr) >4400 Liquid Absorption % by weight (1.0 sp gr) >92 Capillary (wicking height, 575 SSU, 70°F). in. — — Coef. of Friction 0.37 0.37 Vibration Absorption _static load bearing cap/unit area very low Noise Reduction Coef. (1") 0.65 — Noise Reduction Coef. (1") 0.65 — Multen Bursting Strength (1/8"), psi — — Elongation (100 psi), % — — — Hardiness Range, Shore A 5-15 Compressibility (10% Deflection), psi 5-15 <			40
Standard Thickness Range, in. 1/64" thru 4.00" Standard Width, in. 72 Color grey Physical Properties 9 Specific Gravity (%) 17 Therm. Cond. (70F), btu/hr/sq ft/%F/in. 0.25 Therma Expansion 0 Air Perm (1/16"), cfm/sq ft/0.5"H2O 100-200 Liquid Absorption % by weight (1.0 sp gr) >4400 Liquid Absorption % by weight (1.0 sp gr) >4400 Capillary (wicking height, 575 SSU, 70°F). in. — — Coef. of Friction 0.37 Vibration Absorption §tatic load bearing cap/unit area very low Noise Reduction Coef. (1") 0.65 — — — Elongation (100 psi), % — — — — Tensile Strength (min), psi … — — — By oldelection) Site 25 Split Resistance (min,), b/2" width — — Hersile Strength (1/8"), psi 5-15 Scoreyr (within 1 min. after 10% deflection) 99 Abrasion Resistance poor <t< td=""><td colspan="2"></td><td>7.2</td></t<>			7.2
Standard Width, in. 72 Color grey Physical Properties grey Specific Gravity (%) 17 Therm. Cond. (70F), btu/hr/sq ft/°F/in. 0.25 Thermal Expansion 0 Air Perm (1/16"), cfm/sq ft/0.5"HzO 100-200 Liquid Absorption % by weight (1.0 sp gr) >400 Liquid Absorption % by weight (1.0 sp gr) 92 Coef. of Friction			1/64" thru 4.00"
Physical Properties 17 Specific Gravity (%) 17 Therm. Cond. (70F), btu/hr/sq ft/ºF/in. 0.25 Thermal Expansion 0 Air Perm (1/6°), cfm/sq ft/0.5°'H ₂ O 100-200 Liquid Absorption % by weight (1.0 sp gr) >4400 Edition (1/6°), cfm/sq ft/0.5°'H ₂ O 100-200 Capillary (wicking height, 575 SSU, 70°F). in. - Coef. of Friction 0.37 Vibration Absorption static load bearing cap/unit area very low Noise Reduction Coef. (1°) 0.65 Mechanical Properties Tensile Strength (min), psi Tensile Strength (min), psi Hardness Range, Shore A 5.15 Compressibility(10% Deflection), psi 11 Recovery (within 1 min. after 10% deflection) Abrasion Resistance poor Chemical and Environmental Properties 11 Effect of Sunlight and Oxidation Acid Resistance dilute concentrated poor Akkali Resistance			
Specific Gravity (%) 17 Therm. Cond. (70F), btu/hr/sq ft/®F/in. 0.25 Thermal Expansion 0 Air Perm (1/6°), cfm/sq ft/0.5°/H ₂ O 100-200 Liquid Absorption % by weight (1.0 sp gr) >400 Liquid Absorption % by weight (1.0 sp gr) >400 Capillary (wicking height, 575 SSU, 70°F). in. Coef. of Friction 0.37 Vibration Absorption static load bearing cap/unit area very low Noise Reduction Coef. (1°) 0.65 Rechanical Properties Tensile Strength (min), psi Fensile Strength (min), psi Hardness Range. Shore A Split Resistance (min.), lb/2° width Hardness Range. Shore A 5-15 Compressibility(10% Deflection), psi 1 1 Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Effect of Sunlight and Oxidation none Acid Resistance dillute <td colspan="2">Color</td> <td>grey</td>	Color		grey
Specific Gravity (%) 17 Therm. Cond. (70F), btu/hr/sq ft/®F/in. 0.25 Thermal Expansion 0 Air Perm (1/6°), cfm/sq ft/0.5°/H ₂ O 100-200 Liquid Absorption % by weight (1.0 sp gr) >400 Liquid Absorption % by weight (1.0 sp gr) >400 Capillary (wicking height, 575 SSU, 70°F). in. Coef. of Friction 0.37 Vibration Absorption static load bearing cap/unit area very low Noise Reduction Coef. (1°) 0.65 Rechanical Properties Tensile Strength (min), psi Fensile Strength (min), psi Hardness Range. Shore A Split Resistance (min.), lb/2° width Hardness Range. Shore A 5-15 Compressibility(10% Deflection), psi 1 1 Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Effect of Sunlight and Oxidation none Acid Resistance dillute <td>Physical Properties</td> <td></td> <td></td>	Physical Properties		
Thermal Expansion 0 Air Perm (1/16"), cfm/sq ft/0.5"H ₂ O 100-200 Liquid Absorption % by weight (1.0 sp gr) >400 By volume 92 Capillary (wicking height, 575 SSU, 70°F). in. — Coef. of Friction 0.37 Vibration Absorption static load bearing cap/unit area very low Noise Reduction Coef. (1") 0.65 Mechanical Properties — Tensile Strength (min), psi — Tensile Strength (min), psi — Tensile Strength (1/8"), width — Hardness Range, Shore A 5-15 Compressibility(10% Deflection), psi 1 Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Chemical and Environmental Properties poor Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute concentrated fair Acid Resistance dilute concentrated fair			17
Air Perm (1/16"), cfm/sq ft/0.5"H ₂ O 100-200 Liquid Absorption % by weight (1.0 sp gr) >400 Capillary (wicking height, 575 SSU, 70°F). in. Coef. of Friction 0.37 Vibration Absorption static load bearing cap/unit area very low Noise Reduction Coef. (1") 0.65 Mechanical Properties Tensile Strength (min), psi Tensile Strength (min), psi Tensile Strength (1/8"), psi 25 Split Resistance (min.), lb/2" width Hardness Range, Shore A 5-15 Compressibility(10% Deflection), psi 1 Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Chemical and Environmental Properties none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute fair Acid Resistance dilute fair Alkali Resistance dilute fair		0.25	
Liquid Absorption % by weight (1.0 sp gr) >400 By volume 92 Capillary (wicking height, 575 SSU, 70°F). in. — Coef. of Friction 0.37 Vibration Absorption static load bearing cap/unit area very low Noise Reduction Coef. (1") 0.65 Mechanical Properties — Tensile Strength (min), psi — Tensile Strength (min), psi — Tensile Strength (nin), psi — Multen Bursting Strength (1/8"), psi 25 Split Resistance (min.), lb/2" width — Hardness Range, Shore A 5-15 Compressibility (10% Deflection), psi 1 Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute dilute concentrated opoor fair Alkali Resistance dilute	Thermal Expansion	0	
Liquid Absorption % by weight (1.0 sp gr) >400 By volume 92 Capillary (wicking height, 575 SSU, 70°F). in. — Coef. of Friction 0.37 Vibration Absorption static load bearing cap/unit area very low Noise Reduction Coef. (1") 0.65 Mechanical Properties — Tensile Strength (min), psi — Tensile Strength (min), psi — Tensile Strength (nin), psi — Multen Bursting Strength (1/8"), psi 25 Split Resistance (min.), lb/2" width — Hardness Range, Shore A 5-15 Compressibility (10% Deflection), psi 1 Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute dilute concentrated opoor fair Alkali Resistance dilute		100-200	
Capillary (wicking height, 575 SSU, 70°F). in. — Coef. of Friction 0.37 Vibration Absorption static load bearing cap/unit area very low Noise Reduction Coef. (1") 0.65 Mechanical Properties — Tensile Strength (min), psi — Tensile Strength (1/8"), psi 25 Split Resistance (min.), lb/2" width — Hardness Range, Shore A — Compressibility (10% Deflection), psi 1 Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute fair Alkali Resistance dilute fair Alkali Resistance dilute fair	Viewid Absention %	% by weight (1.0 sp gr)	>400
Coef. of Friction 0.37 Vibration Absorption static load bearing cap/unit area very low Noise Reduction Coef. (1") 0.65 Mechanical Properties Tensile Strength (min), psi Elongation (100 psi), % Mullen Bursting Strength (1/8"), psi 25 Split Resistance (min.), lb/2" width Hardness Range, Shore A 5-15 Compressibility(10% Deflection), psi 1 Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute fair Alkali Resistance dilute fair Alkali Resistance dilute fair	Liquid Absorption	By volume	92
Vibration Absorptionstatic load bearing cap/unit areavery lowNoise Reduction Coef. (1")0.65Mechanical Properties0.65Tensile Strength (min), psi–Tensile Strength (min), psi–Elongation (100 psi), %–Mullen Bursting Strength (1/8"), psi25Split Resistance (min.), Ib/2" width–Hardness Range, Shore A5-15Compressibility(10% Deflection), psi1Recovery (within 1 min. after 10% deflection)99Abrasion ResistancepoorChemical and Environmental PropertiesnoneEffect of Sunlight and OxidationnoneSolvent Resistance and Stability in OilexcellentAcid ResistancediluteAlkali ResistancediluteAlkali ResistancediluteInterpretingfairAlkali Resistancelow	Capillary (wicking height, 575 SSU, 70°F). in.		
Vibration Absorption dynamic stress endurance very low Noise Reduction Coef. (1") 0.65 Mechanical Properties — Tensile Strength (min), psi — Tensile Strength (min), psi — Biogration (100 psi), % — Mullen Bursting Strength (1/8"), psi 25 Split Resistance (min.), lb/2" width — Hardness Range, Shore A 5-15 Compressibility(10% Deflection), psi 1 Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Chemical and Environmental Properties poor Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute fair Acid Resistance dilute fair Alkali Resistance dilute fair Oncentrated poor poor	Coef. of Friction		0.37
Noise Reduction Coef. (1")O.65Mechanical PropertiesTensile Strength (min), psiElongation (100 psi), %Mullen Bursting Strength (1/8"), psi25Split Resistance (min), lb/2" widthHardness Range, Shore A5-15Compressibility(10%) Deflection), psi1Recovery (within 1 min. after 10% deflection)99Abrasion ResistancepoorChemical and Environmental PropertiesEffect of Sunlight and OxidationnoneSolvent Resistance and Stability in OilexcellentAcid ResistancediluteAlkali ResistancediluteAlkali ResistancediluteAlkali ResistancediluteImage: ConcentratedpoorImage: ConcentratedpoorImage: ConcentratedfairImage: Concentratedfair <td rowspan="2">Vibration Absorption</td> <td>static load bearing cap/unit area</td> <td>very low</td>	Vibration Absorption	static load bearing cap/unit area	very low
Mechanical Properties — Tensile Strength (min), psi — Elongation (100 psi), % — Mullen Bursting Strength (1/8"), psi 25 Split Resistance (min.), lb/2" width — Hardness Range, Shore A 5-15 Compressibility(10% Deflection), psi 1 Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Chemical and Environmental Properties none Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute fair concentrated poor fair Alkali Resistance dilute fair oncentrated low fair		dynamic stress endurance	very low
Tensile Strength (min), psiElongation (100 psi), %Mullen Bursting Strength (1/8"), psi25Split Resistance (min.), lb/2" widthHardness Range, Shore A5-15Compressibility(10% Deflection), psi1Recovery (within 1 min. after 10% deflection)99Abrasion ResistancepoorChemical and Environmental PropertiesEffect of Sunlight and OxidationnoneSolvent Resistance and Stability in OilexcellentAcid ResistancediluteAlkali ResistancediluteAlkali ResistancediluteIntermentationfairIntermentationpoorIntermentationfair	Noise Reduction Coef. (1")		0.65
Tensile Strength (min), psiElongation (100 psi), %Mullen Bursting Strength (1/8"), psi25Split Resistance (min.), lb/2" widthHardness Range, Shore A5-15Compressibility(10% Deflection), psi1Recovery (within 1 min. after 10% deflection)99Abrasion ResistancepoorChemical and Environmental PropertiesEffect of Sunlight and OxidationnoneSolvent Resistance and Stability in OilexcellentAcid ResistancediluteAlkali ResistancediluteAlkali ResistancediluteIntermentationfairIntermentationpoorIntermentationfair	Mechanical Properties		
Mullen Bursting Strength (1/8"), psi 25 Split Resistance (min.), lb/2" width Hardness Range, Shore A 5-15 Compressibility(10% Deflection), psi 1 Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Chemical and Environmental Properties none Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute fair Alkali Resistance dilute fair Output fair poor	Tensile Strength (min), psi		_
Split Resistance (min.), Ib/2" width Hardness Range, Shore A 5-15 Compressibility(10% Deflection), psi 1 Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Chemical and Environmental Properties poor Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute fair Alkali Resistance dilute fair Oncentrated poor joor	Elongation (100 psi), %		_
Hardness Range, Shore A 5-15 Compressibility(10% Deflection), psi 1 Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Chemical and Environmental Properties Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute Acid Resistance dilute Acid Resistance dilute Acid Resistance lilute Acid Resistance dilute Acid Resistance lilute Acid Resistance lilute Alkali Resistance lilute Alkali Resistance lilute Alkali Resistance lilute Image: Concentrated low	Mullen Bursting Strength (1/8"	25	
Compressibility(10% Deflection), psi 1 Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Chemical and Environmental Properties Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute fair Alkali Resistance dilute fair Or Chemical and Environmentated poor fair	Split Resistance (min.), Ib/2"	width	_
Recovery (within 1 min. after 10% deflection) 99 Abrasion Resistance poor Chemical and Environmental Properties none Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute fair Acid Resistance dilute fair Alkali Resistance dilute fair Image: Alkali Resistance boor fair Image: Alkali Resistance dilute fair Image: Alkali Resistance boor fair Image: Alkali Resistance dilute fair Image: Alkali Resistance dilute fair Image: Alkali Resistance dilute fair	Hardness Range, Shore A		5-15
Abrasion Resistance poor Chemical and Environmental Properties none Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute fair Acid Resistance dilute fair Alkali Resistance dilute fair Image: Alkali Resistance boor fair Image: Alkali Resistance dilute fair			1
Provide and properties Chemical and Environmental Properties Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute fair Acid Resistance dilute fair Alkali Resistance dilute fair Output fair fair Image: oncentrated fair fair Output fair fair Image: oncentrated fair fair	Recovery (within 1 min. after	99	
Effect of Sunlight and Oxidation none Solvent Resistance and Stability in Oil excellent Acid Resistance dilute fair Concentrated poor Alkali Resistance dilute fair Image: oncentrated fair fair Image: oncentrated fair fair Image: oncentrated fair fair	Abrasion Resistance	poor	
Solvent Resistance and Stability in Oil excellent Acid Resistance dilute fair concentrated poor Alkali Resistance dilute fair ocncentrated low	Chemical and Environm	nental Properties	
Acid ResistancedilutefairAcid ResistanceconcentratedpoorAlkali Resistancedilutefairconcentratedlow			none
Acid Resistance concentrated poor Alkali Resistance dilute fair concentrated low	Solvent Resistance and Stability in Oil		excellent
Alkali Resistance dilute fair Image: Concentrated Image: Concentrated Image: Concentrated	Acid Resistance	dilute	fair
Alkali Resistance low		concentrated	poor
concentrated low		dilute	fair
Temperature Range, °F - 80 to +200		concentrated	low
	Temperature Range, °F		- 80 to +200

Auburn has more than 250 different gasket materials in stock for your immediate delivery!

Considering Diecut Parts Gaskets and Seals Cushions, Pads, & Bumpers Die-Cut Shapes Adhesive-Backed Gaskets Explore Soft Gasket Materials Full Gasket Material List Product Data Sheets High Temperature Gasketing Sponge & Foam Materials View Products & Services Custom Part Categories Manufacturing Capabilities Company Overview Quality Policy