



PRODUCT NEWS

Auburn Manufacturing Company

29 Stack Street, Middletown, CT 06457
PHONE 860-346-6677 FAX 806-346-1334
Email: info@auburn-mfg.com
Website: www.auburn-mfg.com

ABRASION RESISTANT RED RUBBER (SBR) 75 Durometer

Red Rubber from Auburn is an economical SBR rubber sheet designed for use in low pressure applications with no oil resistance requirements. Commonly used for gaskets and seals; tires, conveyor belts, and chutes, SBR (styrene butadiene rubber) is harder and offers better abrasion resistance than natural rubber. It is also known as skirtboard.

Temperature Range: -20°F to +170°F

- Width: 36", 48", 72"
- Trim: Trimmed
- Finish: Smooth
- Color: Red - Also available in Black on a special order basis.

Typical Properties:

Durometer Hardness (Shore A ± 5)	Product Number	Thickness (inches)	Tensile (psi)	Ultimate Elongation (%)	Estimated Weight per Linear Foot (1/8" X 36")	Specifications
	Compound		Minimum	Minimum		
75	AUB75RR	.031 - .250	400	150	3.5 LB	ASTM D 1330 Grade 2, ASTM D 2000 1AA 704 Z1 (Z1 = 75 ± 5 Durometer)
	SBR					

These typical physical properties are provided for evaluation information only. It is up to the end-user to determine the appropriate material for the intended application.