



PRODUCT NEWS

Auburn Manufacturing Company

29 Stack Street, Middletown, CT 06457
PHONE 860-346-6677 FAX 806-346-1334
Email: info@auburn-mfg.com
Website: www.auburn-mfg.com

PREMIUM EPDM 40-80 DUROMETER

Premium EPDM Rubber from Auburn is a High Grade EPDM suited for applications where a high performance rating is required. It exhibits excellent resistance to heat, ozone and sunlight and has good temperature flexibility.

Temperature Range: -40°F to +220°F

- Width: 36", 48"
- Trim: Trimmed
- Finish: Smooth
- Color: Black

Typical Properties:

Durometer Hardness (Shore A ± 5)	Product Number	Thickness (inches)	Tensile (psi)	Ultimate Elongation (%)	Estimated Weight per Linear Foot (1/8" X 36") (lb)	Specifications
40	AUB40EPDM	.031 – .250	1050	400	2.03	ASTM D 2000 M2BA 407 C12 F17
50	AUB50EPDM	.031 – .250	1500	400	2.2	ASTM D 2000 3BA 515 B13 C12 F17, SAE J200 3BA 515 B13 C12 F17, MIL-R-3065 RS 515 C1 F1
60	AUBD60EPDM	.031 – .250	1500	350	2.2	ASTM D 2000 3BA 615 B13 C12 F17, SAE J200 3BA 615 B13 C12 F17 MIL-R-3065 RS 615 C1 F1
70	AUB70EPDM	.031 – .250	1500	250	2.2	ASTM D 2000 3BA 715 B13 C12 F17, SAE J200 3BA 715 B13 C12 F17, MIL-R-3065 RS 715 C1 F1
80	AUB80EPDM	.031 – .250	1500	150	2.2	ASTM D 2000 3BA 815 B13 C12 F17, SAE J200 3BA 815 B13 C12 F17, MIL-R-3065 RS 815 C1 F1

These typical physical properties are provided for evaluation information only.
It is up to the end-user to determine the appropriate material for the intended application.

GASKETS • PADS • SHEETS • ROLLS • SHIMS • SEALS • TAPES